



MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A

BENEFIT CANADA TO THE

A MANAGE AND SELECTION OF THE PROPERTY OF THE

A134912



THE OBJECTIVE EVALUATION OF AIRCREW PROTECTIVE BREATHING EQUIPMENT: V. MASK/GOGGLES COMBINATIONS FOR FEMALE CREWMEMBERS

D. deSteiguer J. T. Saldivar E. A. Higgins G. E. Funkhouser

Civil Aeromedical Institute Federal Aviation Administration Oklahoma City, Oklahoma



July 1983

Document is available to the public through the National Technical Information Service Springfield, Virginia 22161

> Prepared for U.S. DEPARTMENT OF TRANSPORTATION Federal Aviation Administration Office of Aviation Medicine Washington, D.C. 20591



E

NOTICE

This document is disseminated under the sponsorship of the Department of Transportation in the interest of information exchange. The United States Government assumes no liability for the contents or use thereof.

		, ,		
1. Report No. 2	. Government Acces	sion No. 3. R	ecipient's Catalog N	lo.
FAA-AM-83-14	AIZH	912		
4. Title and Subtitle		5. R	eport Date	
THE OBJECTIVE EVALUATION OF	ATRCREW PROTE	CTIVE Ju	ıly 1983	
BREATHING EQUIPMENT: V. MASI			erforming Organizatio	on Code
FOR FEMALE CREWMEMBERS	.,, 0000222			
		8. P.	erforming Organizatio	on Report No.
7. Author's) D. deSteiguer, J. T.	Saldivar, E.	A. Higgins		
and G. E. Funkhouser				
9. Performing Organization Name and Address		10. V	Vork Unit No. (TRAI	S)
FAA Civil Aeromedical Institu	ute			
P.O. Box 25082	25	11. 3	Contract or Grant No	•
Oklahoma City, Oklahoma 7313	25	13 7	ype of Report and P	
12. Sponsoring Agency Name and Address			pe of Report and P	eriod Covered
Office of Aviation Medicine				
Federal Aviation Administrat:	ion			
800 Independence Avenue, S.W.		14. S	ponsoring Agency Co	ode
Washington, D.C. 20591	•			
15. Supplementary Notes				
Research leading to preparat:	ion of this r	eport was performe	ed under task	s
AM-B-81-PRS-13 and AM-B-82-P	RS-13.			
16. Abstract				
The acceptance criteria for subjects to maintain a contain simultaneously 0.1 or less in goggle combinations tested with criteria for adequate protect and female subjects suggest ences in cranial and facial of the subjects in the subject in the subje	minant ration the goggle ith female sution. Comparthat the fail	of 0.05 or less in while wearing eyes bjects, 8 failed tison tests on anth	n the oxygenglasses. Of comeet the animopometric d	mask and/or the 23 mask/ acceptance lata from male
17. Key Words		18. Distribution Statement		
Crewmember, Protective Breath Anthropometric Considerations	٠,	Document is available through the Nation Information Service Virginia 22161	nal Technical	L
19. Security Classif. (of this report)	20. Security Class	if, (of this page)	21- No. of Pages	22. Price
Unclassified	Unclassi	fied	7	

TABLE OF CONTENTS

germent and the tree	
ä	
•	
	TABLE OF CONTENTS
	Page
	INTRODUCTION
	METHODS
	RESULTS
	SUMMARY
	REFERENCES
** **	
	Accession For
	NTIS GRA&I DTIC TAB
	DTIC TAB Unannounced
	Justification
<u> </u>	Ву
	Distribution/

Acces	sion For	r
NTIS	GRA&I	M
DTIC	TAB	
Unann	ounced	
Justi	fication	
Ву		
Distr	ibution,	1
Avai	lability	Codes
	Avail a	nd/or
Dist	Speci	a l
A 1		
/1-/		

THE OBJECTIVE EVALUATION OF AIRCREW PROTECTIVE BREATHING EQUIPMENT: V. MASK/GOGGLES COMBINATIONS FOR FEMALE CREWMEMBERS

INTRODUCTION

The requirements for protective breathing devices and the rationale for equipment selection have been reviewed in previous publications (1,2,3,4). These same publications also presented the results of contaminant leak testing of 118 mask/goggles combinations designed for use by flight deck crewmembers. The acceptance criteria for the mask/goggles combinations were for 10 of 12 test subjects to maintain a contaminant ratio of 0.05 or less in the oxygen mask and/or simultaneously 0.1 or less in the goggles while wearing eyeglasses (2,4). These criteria were developed at joint meetings between the Federal Aviation Administration (FAA) and industry representatives held in Los Angeles, California, August 1974, and in Washington, D.C., September 1974 (5). Of the 118 mask/goggles combinations tested, 106 failed to meet the acceptance criteria. These tests demonstrated the necessity for venting the goggles, the need for application of some amount of positive pressure within the equipment, very high cylinder drainage rates for most combinations tested with positive pressure, and significant donning problems for goggles equipped with venting tubes.

At the request of the FAA Flight Standards Service, the testing program was continued to support the development of protective breathing devices that would meet the approved performance criteria. As a result of this test program, several major manufacturers and suppliers of oxygen mask/goggles combinations initiated developmental programs in an effort to correct the identified deficiencies.

This report presents the results of an evaluation made to determine the effectiveness of 23 mask/goggles/regulator combinations in providing protection for the female crewmember. Criteria evaluated include pass/fail ratios for the various combinations, cylinder drainage rates, and the influence of regulator delivery pressure on cylinder drainage. Since females generally have smaller facial dimensions than do males, and since most mask/goggles combinations are sized to fit the male face, a comparison between selected anthropometric parameters was made to determine the influence of face size on the pass/fail ratio of the various combinations tested.

METHODS

The general analytical method developed for testing of protective breathing equipment has been described elsewhere (4). Briefly, a simple exposure chamber of sufficient size to accommodate a subject and the equipment to be tested was used to contain the challenge atmosphere of 120 ppm n-pentane. Small needles were inserted into the protective breathing device and the goggles to provide for the collection of gas samples from specific locations. Small-bore flexible tubing, passed through the chamber wall, connected the sample needles to a selector valve located outside the chamber. The sample gas was drawn through a twin-loop collector valve where a known aliquot was collected and delivered to a gas chromatograph equipped with a

hydrogen flame ionization detector. Nonexaggerated eyeglasses were worn by all subjects during testing. American Optical Corporation frames F9848SM, ranging in size from $46 \times 20 \text{ mm}$ to $48 \times 22 \text{ mm}$, with plano lenses were used.

The subject population consisted of 23 females trained in test procedures and equipment use. Selected anthropometric measurements were taken for each subject and compared to measurements made on male subjects in prior evaluation tests (4). Eleven types of oxygen masks and five types of goggles were tested. All of these devices were designed for use with some amount of positive pressure applied to the mask. Four aircraft oxygen regulators, two maskmounted and two panel-mounted, were used to provide pressure to the masks.

The protective breathing devices submitted by the Robertshaw Controls Company consisted of standard aviator's crew oxygen masks, goggles equipped with venting tubes that require positioning within the cone of the oxygen mask, and a Robertshaw mask-mounted regulator. The goggles (two pairs) differed only in the suspension strap--one pair having an adjustable head strap, and the other pair having a nonadjustable strap. The venting tubes included internal soft wires which provided for forming and positioning the tubes. In addition, the venting tubes had flow orifices approximately 1 in from the tube ends.

The devices submitted by the Sierra Engineering Company consisted of standard Sierra crew oxygen masks and a prototype, S/N 358-1028V, designed to fit the smaller dimensions of the female face. All masks were modified to include manually activated flow valves in the upper portion of the nose cups. These valves, when opened, and with positive pressure applied to the mask, directed a venting flow of air into the goggles. The goggles were a standard Sierra product. A Robertshaw mask-mounted regulator and two Bendix panel-mounted regulators were used for testing Sierra equipment.

The devices submitted by the Puritan Equipment Company consisted of standard Puritan crew oxygen masks modified to include automatically activated flow valves in the upper portion of the nose cups. These valves, when opened by the pressure of the goggles and with positive pressure applied to the mask, directed a venting flow into the goggles. The goggles were a new Puritan product. A Robertshaw mask-mounted regulator and two Bendix panel-mounted regulators were used for testing the equipment.

The protective breathing devices submitted by the Scott Company consisted of an Eros mask provided with a mask-mounted regulator and a manually activated valve which provided venting to the goggles. The mask is of a quick-don type which utilizes the aircraft oxygen system to inflate an expandable harness by means of a triggering mechanism positioned under the nose cup. The harness is then slipped over the head and the triggering mechanism released, resulting in a deflation of the harness which secures the mask to the face. The goggles provided were an experimental model designed specifically to fit the mask.

CONTROL OF THE PROPERTY OF THE

RESULTS

Of the 23 mask/goggles combinations tested, 8 failed to meet the accepted criteria of maintaining a contaminant ratio of less than 0.1 for the goggles and simultaneously 0.05 in the mask when there were 3 failures in 12 or fewer tests (Table 1). All of these failures were attributed to failures in the goggles. Several identifiable factors contributed to these failures.

TABLE 1. Types of Mask/Goggles Combinations Tested and a Summary of the Results

Robertshaw Controls Company

	ROBET	LSHaw Contro	15 Company				
Mask P/N	Goggles P/N	Regulator	Pressure in H20*	Pass/Fail	Cylinder Drainage (L/min)		
595-900-051	595-900-058	Robertshaw	1.7	11/1	15.2		
595-900-051	595-900-057	Robertshaw	1.7	11/1	11.3		
595-900-049-01		Robertshaw	1.7	11/1	10.7		
595-900-049-01		Robertshaw	1.7	10/2	12.3		
595-900-046	595-900-058	Robertshaw	1.7	11/1	9.6		
595-900-046	595-900-057	Robertshaw	1.7	11/2	9.5		
595-900-029	595-900-058	Robertshaw	1.7	12/0	12.7		
595-900-029	595-900-057	Robertshaw	1.7	12/0	11.0		
	Sier	ra Engineeri	ng Company				
358-1028V**	322-01	Robertshaw	1.7	12/0	10.2		
358-1028V**	322-01	Bendix	1.5	11/1	9.3		
358-1028V**	322-01	Bendix	3.5	9/3	15.9		
358-1025	322-01	Robertshaw	1.7	10/2	9.3		
358-1025	322-01	Bendix	1.5	10/2	8.3		
358-1025	322-01	Bendix	3.5	10/2	11.0		
358-1223	322-01	Robertshaw	1.7	8/4	12.6		
358-1223	322-01	Bendix	1.5	8/4	8.8		
358-1223	322-01	Bendix	3.5	8/4	18.7		
	Puri	tan Equipmen	t Company				
114322-03	118072-01	Robertshaw	1.7	10/2	18.2		
114120-51	118072-01	Bendix	1.5	4/6	10.3		
114120-51	118072-01	Bendix	3.5	8/5	25.8		
114020-40	118072-01	Robertshaw	1.7	8/4	10.4 n For		
114020-40	118072-01	Bendix	1.5	12/0	8.3 .227		
Scott Company							
Eros	36864-21	Eros	1.8	9/3	ce∂ 9.0ati		
(MC-1022-EX)	(MXP-210)			-,-			
	By Discountien						
*1 in H ₂ 0 = 0.249 kN/M ²							
**Not tested or	n male subjec	ts		1	Avoi bility doing		
					Dist Special		

Among those noted most often were a failure of the goggles to mate with the contour of the oxygen mask, gaps caused by penetration of the eyeglasses frames at the goggles/temple interface, and improper goggles/face mating due to either goggles design or the facial dimensions of the subject.

It would appear that the data in Table 1 indicate a much higher failure rate for the 3.5 in H₂O pressure regulator than for the two lower pressures (1.5 and 1.7 in H₂O). But, in order to make meaningful comparisons for the failure rates between the highest pressure and the two lower pressures, the data should be evaluated only for those mask/goggles combinations tested using the highest pressure regulator and at least one of the two lower pressure regulators. There are four such mask/goggles combinations listed in the table. The results are summarized below.

			Pass/Fail	by Regula	tor Pressure
Company	Mask P/N	Goggles P/N	1.5	1.7	3.5
Sierra Engineer- ing Company	358-1028V	322-01	(The 3.5)	12/0 pressure h failure ra	ad the
	358-1025	322-01	(The fail		10/2 were identi- pressures.)
358-1223 322		322-01	(The fail		8/4 were identi- pressures.)
Puritan Equip- ment Company	114120-51	118072-01	(The 3.5)	N/A pressure h ilure rate	ad the

Thus, a higher failure rate for the 3.5 in pressure is evident in only one mask/goggles combination; it is the same for two combinations; and it is actually lower for one combination. Therefore, we cannot state that the failure rate for the highest pressure is consistently greater.

For all of the other mask/goggles combinations there were only one or two of the lower pressures used and no data were available from the highest pressure regulator. Therefore, no comparisons could be made. It is evident from the data, however, that those mask/goggles combinations which did not use the highest pressure regulator, had better pass/fail ratios than those combinations tested using the 3.5 in H₂O pressure regulator. But, because the lower pressures produced failure rates similar to the highest pressure's rates when tested with identical mask/goggles combinations, the amount of pressure delivered to the mask/goggles probably had little effect on the failure rate. The differences seen are most likely due to the differences in the design and the fit of the various mask/goggles combinations.

Comparisons of the facial and cranial dimensions of the female subjects used in this study (Table 2) to those of U.S. Air Force women (7) showed them to be generally within the 5th to 95th percentiles of the reference population. However, when the same data were compared to the anthropometric measurements of the group of male subjects used in the prior test to evaluate the mask/goggles/regulator combinations (4), it was found that the dimensions of the male face and cranium were larger for all selected parameters than those of the females, and that the differences were statistically significant at the p <.05 level (Table 3).

TABLE 2. Selected Anthropometric Measurements, in Millimeters, of Subject Population Compared to U.S. Air Force Women (1972)

Subject	Head	Head	Face	Face
No.	Length	Breadth	<u>Length</u>	Breadth
•	200	1/0	100	107
1 2 3	200	148	108	126
2	181	139	109	123
	193	156	105	136
4	184	155	109	135
5 6 7	191	145	108	128
о 7	188	140	112	126
/	184	140	111	127
8	193	148	111	134
9	195	151	104	136
10	183	144	100	127
11	190	150	115	134
12	189	145	118	131
13	186	141	113	124
14	185	142	113	130
15	187	140	113	128
16	179	147	106	134
17	180	147	107	136
18	192	154	103	141
19	197	147	114	130
20	175	142	101	128
21	192	149	120	135
22	197	149	108	138
23	189	144	109	122
U.S. Air F	orce Women (1972)			
5%	173	135	96	119
95%	195	155	117	138

TABLE 3. Comparison* of Selected Anthropometric Measurements, in Millimeters, of Female and Male Subjects

Parameter	N	Mean	S.D.	t	<u> </u>
Head Length					
Female Male	23 12	188 198	6 4	4.93	<.05
Head Breadth					
Female Male	23 12	146 153	5 3	4.42	<.05
Face Length					
Female Male	23 12	109 120	5 7	5.32	<.05
Face Breadth					
Female Male	23 12	131 141	5 4	5.60	<.05

^{*}Analysis of variance, two independent samples

SUMMARY

With modern aircraft operating at ever-increasing altitudes, the performance and facial fit of crew oxygen masks becomes more critical if acceptable protection is to be provided. In addition, the possibility of toxic cargo spills, or the possibility of in-flight fires with the release of toxic combustion products and smoke, make protection of the visual processes another important factor for consideration in the design of protective equipment for crewmembers. The increasing number of female pilots in the civil air fleet make it imperative that existing equipment, as well as new designs, be evaluated for their suitability and efficiency in affording protection to the female crewmember.

Several of the protective breathing devices included in this study that provided venting to the goggles by means of a valve incorporated into the mask have passed the proposed acceptance criteria, are reasonably easy to don, and do not cause high cylinder drainage rates. These systems have been designed so as not to compromise the oxygen mask when used for decompression purposes. Every protective breathing device that has passed the proposed acceptance criteria has required some amount of positive pressure within the device. Therefore, a regulator with positive pressure output probably should be included in the system and the regulator outlet pressure specified for a given system. If the regulator does not provide positive pressure

automatically, the crewmember should be trained to manually set the regulator to 100 percent oxygen and to positive (emergency) pressure.

Every mask/goggles combination tested in this study had passed the proposed acceptance criteria for male subjects in the prior study (6). The comparative statistical analyses of the anthropometric data gathered from male and female subjects suggest that improper sizing of protective equipment was the cause for failures. To provide adequate protection for both sexes will require: (1) equipment that will accommodate the different facial and cranial sizes, or (2) different sized equipment for the two groups.

REFERENCES

- 1. deSteiguer, D., E. B. McFadden, M. S. Pinski, and J. R. Bannister: The Use of n-Pentane as a Tracer Gas for the Quantitative Evaluation of Aircrew Protective Breathing Equipment, SAFE Symposium, San Diego, California, 1976.
- deSteiguer, D., M. S. Pinski, J. R. Bannister, and E. B. McFadden: The Objective Evaluation of Aircrew Protective Breathing Equipment: I. Oxygen Mask/Goggles Combinations, SAFE Symposium, San Diego, California, 1976.
- deSteiguer, D., M. S. Pinski, J. R. Bannister, and E. B. McFadden: The Objective Evaluation of Aircrew Protective Breathing Equipment: II. Fullface Masks and Hoods, SAFE Symposium, San Diego, California, 1976.
- 4. deSteiguer, D., M. S. Pinski, J. R. Bannister, and E. B. McFadden: Aircrew and Passenger Protective Breathing Equipment Studies, FAA Office of Aviation Medicine Report No. FAA-AM-78-4, 1978.
- 5. deSteiguer, D., M. S. Pinski, J. R. Bannister, and E. B. McFadden: An Objective Evaluation of Smoke Protective Equipment Designed for Use by Aircraft Crewmembers. Memorandum Report No. AAC-119-75-5(S), July 1975 (unpublished).
- 6. deSteiguer, D., M. S. Pinski, and E. B. McFadden: The Objective Evaluation of Aircrew Protective Breathing Equipment: III. Improved Types of Mask/Goggles Combinations, SAFE Symposium, Jan Diego, California, 1976.
- Clauser, C. E., et al., Anthropometry of Air Force Women, United States Air Force Aerospace Medical Division Report No. AMRL-TR-70-5, April 1972.

FILMED